

Package ‘starnet’

September 20, 2024

Version 0.0.7

Title Stacked Elastic Net

Description Implements stacked elastic net regression (Rauschenberger 2021, <[doi:10.1093/bioinformatics/btaa535](https://doi.org/10.1093/bioinformatics/btaa535)>). The elastic net generalises ridge and lasso regularisation (Zou 2005, <[doi:10.1111/j.1467-9868.2005.00503.x](https://doi.org/10.1111/j.1467-9868.2005.00503.x)>). Instead of fixing or tuning the mixing parameter alpha, we combine multiple alpha by stacked generalisation (Wolpert 1992 <[doi:10.1016/S0893-6080\(05\)80023-1](https://doi.org/10.1016/S0893-6080(05)80023-1)>).

Depends R (>= 3.0.0)

Imports glmnet, survival, cornet, Matrix

Suggests knitr, testthat, rmarkdown

Enhances CVXR, mvtnorm

VignetteBuilder knitr

License GPL-3

Language en-GB

RoxygenNote 7.3.2

Encoding UTF-8

URL <https://github.com/rauschenberger/starnet>

BugReports <https://github.com/rauschenberger/starnet/issues>

NeedsCompilation no

Author Armin Rauschenberger [aut, cre]

Maintainer Armin Rauschenberger <armin.rauschenberger@uni.lu>

Repository CRAN

Date/Publication 2024-09-20 09:00:02 UTC

Contents

starnet-package	2
.cv.glmnet	3
.loss	3

.simulate	4
coef.starnet	4
cv.starnet	5
glmnet.auc	6
predict.starnet	7
print.starnet	8
starnet	9
weights.starnet	10
Index	12

starnet-package	<i>Stacked Elastic Net Regression</i>
-----------------	---------------------------------------

Description

The R package starnet implements stacked elastic net regression. The elastic net generalises ridge and lasso regularisation. Instead of fixing or tuning the mixing parameter alpha, we combine multiple alphas by stacked generalisation.

Details

Use function `starnet` for model fitting. Type `library(starnet)` and then `?starnet` or `help("starnet")` to open its help file.

See the vignette for further examples. Type `vignette("starnet")` or `browseVignettes("starnet")` to open the vignette.

Author(s)

Maintainer: Armin Rauschenberger <armin.rauschenberger@uni.lu>

References

A Rauschenberger, E Glaab, and MA van de Wiel (2021). "Predictive and interpretable models via the stacked elastic net". *Bioinformatics*. 37(14):2012-2016. doi:10.1093/bioinformatics/btaa535. <armin.rauschenberger@uni.lu>

See Also

Useful links:

- <https://github.com/rauschenberger/starnet>
- Report bugs at <https://github.com/rauschenberger/starnet/issues>

.cv.glmnet	<i>glmnet::cv.glmnet</i>
------------	--------------------------

Description

Wrapper for [cv.glmnet](#), with different handling of sparsity constraints.

Usage

```
.cv.glmnet(..., nzero)
```

Arguments

...	see cv.glmnet
nzero	maximum number of non-zero coefficients: positive integer

Value

Object of class [cv.glmnet](#).

Examples

```
NA
```

.loss	<i>Loss</i>
-------	-------------

Description

Calculate loss from predicted and observed values

Usage

```
.loss(y, x, family, type.measure, foldid = NULL, grouped = TRUE)
```

Arguments

y	observed values: numeric vector of length n
x	predicted values: numeric vector of length n
family	character "gaussian", "binomial", "poisson", "mgaussian", or "multinomial" (to implement: "cox")
type.measure	character "deviance", "mse", "mae", "class", or "auc"
foldid	fold identifiers: integer vector of length n , or NULL
grouped	logical (for "cox" only)

Examples

NA

`.simulate`*Simulation*

Description

Functions for simulating data

Usage`.simulate.block(n, p, mode, family = "gaussian")`**Arguments**

<code>n</code>	sample size: positive integer
<code>p</code>	dimensionality: positive integer
<code>mode</code>	character "sparse", "dense" or "mixed"
<code>family</code>	character "gaussian", "binomial" or "poisson"

ValueList of vector y and matrix X .**Examples**

NA

`coef.starnet`*Extract Coefficients*

Description

Extracts pooled coefficients. (The meta learners weights the coefficients from the base learners.)

Usage

```
## S3 method for class 'starnet'
coef(object, nzero = NULL, ...)
```

Arguments

object [starnet](#) object
nzero maximum number of non-zero coefficients: positive integer, or NULL
... further arguments (not applicable)

Value

List of scalar alpha and vector beta, containing the pooled intercept and the pooled slopes, respectively.

Examples

```
set.seed(1)
n <- 50; p <- 100
y <- rnorm(n=n)
X <- matrix(rnorm(n*p), nrow=n, ncol=p)
object <- starnet(y=y, X=X)
coef <- coef(object)
```

cv.starnet

Model comparison

Description

Compares stacked elastic net, tuned elastic net, ridge and lasso.

Usage

```
cv.starnet(
  y,
  X,
  family = "gaussian",
  nalpha = 21,
  alpha = NULL,
  nfolds.ext = 10,
  nfolds.int = 10,
  foldid.ext = NULL,
  foldid.int = NULL,
  type.measure = "deviance",
  alpha.meta = 1,
  nzero = NULL,
  intercept = NULL,
  upper.limit = NULL,
  unit.sum = NULL,
  ...
)
```

Arguments

<code>y</code>	response: numeric vector of length n
<code>X</code>	covariates: numeric matrix with n rows (samples) and p columns (variables)
<code>family</code>	character "gaussian", "binomial" or "poisson"
<code>nalpha</code>	number of alpha values
<code>alpha</code>	elastic net mixing parameters: vector of length <code>nalpha</code> with entries between 0 (ridge) and 1 (lasso); or NULL (equidistance)
<code>nfolds.ext</code> , <code>nfolds.int</code> , <code>foldid.ext</code> , <code>foldid.int</code>	number of folds (<code>nfolds</code>): positive integer; fold identifiers (<code>foldid</code>): vector of length n with entries between 1 and <code>nfolds</code> , or NULL, for hold-out (single split) instead of cross-validation (multiple splits): set <code>foldid.ext</code> to 0 for training and to 1 for testing samples
<code>type.measure</code>	loss function: character "deviance", "class", "mse" or "mae" (see cv.glmnet)
<code>alpha.meta</code>	meta-learner: value between 0 (ridge) and 1 (lasso) for elastic net regularisation; NA for convex combination
<code>nzero</code>	number of non-zero coefficients: scalar/vector including positive integer(s) or NA; or NULL (no post hoc feature selection)
<code>intercept</code> , <code>upper.limit</code> , <code>unit.sum</code>	settings for meta-learner: logical, or NULL (<code>intercept=!is.na(alpha.meta)</code> , <code>upper.limit=TRUE</code> , <code>unit.sum=is.na(alpha.meta)</code>)
<code>...</code>	further arguments (not applicable)

Value

List containing the cross-validated loss (or out-of sample loss if `nfolds.ext` equals two, and `foldid.ext` contains zeros and ones). The slot `meta` contains the loss from the stacked elastic net (`stack`), the tuned elastic net (`tune`), ridge, lasso, and the intercept-only model (`none`). The slot `base` contains the loss from the base learners. And the slot `extra` contains the loss from the restricted stacked elastic net (`stack`), lasso, and lasso-like elastic net (`enet`), with the maximum number of non-zero coefficients shown in the column name.

Examples

```
loss <- cv.starnet(y=y, X=X)
```

```
glmnet.auc
```

```
glmnet:::auc
```

Description

Import of [auc](#) (internal function)

Usage

```
glmnet.auc(y, prob, w)
```

Arguments

y	observed classes
prob	predicted probabilities
w	(ignored here)

Value

area under the ROC curve

Examples

NA

predict.starnet	<i>Makes Predictions</i>
-----------------	--------------------------

Description

Predicts outcome from features with stacked model.

Usage

```
## S3 method for class 'starnet'
predict(object, newx, type = "response", nzero = NULL, ...)
```

Arguments

object	starnet object
newx	covariates: numeric matrix with <i>n</i> rows (samples) and <i>p</i> columns (variables)
type	character "link" or "response"
nzero	maximum number of non-zero coefficients: positive integer, or NULL
...	further arguments (not applicable)

Value

Matrix of predicted values, with samples in the rows, and models in the columns. Included models are alpha (fixed elastic net), ridge (i.e. alpha0), lasso (i.e. alpha1), tune (tuned elastic net), stack (stacked elastic net), and none (intercept-only model).

Examples

```
set.seed(1)
n <- 50; p <- 100
y <- rnorm(n=n)
X <- matrix(rnorm(n*p), nrow=n, ncol=p)
object <- starnet(y=y, X=X)
y_hat <- predict(object, newx=X[c(1),, drop=FALSE])
```

print.starnet

Print Values

Description

Prints object of class [starnet](#).

Usage

```
## S3 method for class 'starnet'
print(x, ...)
```

Arguments

x [starnet](#) object
... further arguments (not applicable)

Value

Prints "stacked gaussian/binomial/poisson elastic net".

Examples

```
set.seed(1)
n <- 50; p <- 100
y <- rnorm(n=n)
X <- matrix(rnorm(n*p), nrow=n, ncol=p)
object <- starnet(y=y, X=X)
print(object)
```

starnet	<i>Stacked Elastic Net Regression</i>
---------	---------------------------------------

Description

Implements stacked elastic net regression.

Usage

```
starnet(
  y,
  X,
  family = "gaussian",
  nalpha = 21,
  alpha = NULL,
  nfolds = 10,
  foldid = NULL,
  type.measure = "deviance",
  alpha.meta = 1,
  penalty.factor = NULL,
  intercept = NULL,
  upper.limit = NULL,
  unit.sum = NULL,
  ...
)
```

Arguments

y	response: numeric vector of length n
X	covariates: numeric matrix with n rows (samples) and p columns (variables)
family	character "gaussian", "binomial" or "poisson"
nalpha	number of alpha values
alpha	elastic net mixing parameters: vector of length nalpha with entries between 0 (ridge) and 1 (lasso); or NULL (equidistance)
nfolds	number of folds
foldid	fold identifiers: vector of length n with entries between 1 and nfolds; or NULL (balance)
type.measure	loss function: character "deviance", "class", "mse" or "mae" (see cv.glmnet)
alpha.meta	meta-learner: value between 0 (ridge) and 1 (lasso) for elastic net regularisation; NA for convex combination
penalty.factor	differential shrinkage: vector of length n with entries between 0 (include) and Inf (exclude), or NULL (all 1)
intercept, upper.limit, unit.sum	settings for meta-learner: logical, or NULL (intercept=!is.na(alpha.meta), upper.limit=TRUE, unit.sum=is.na(alpha.meta))
...	further arguments passed to glmnet

Details

Post hoc feature selection: consider argument `nzero` in functions `coef` and `predict`.

Value

Object of class `starnet`. The slots `base` and `meta` contain `cv.glmnet`-like objects, for the base and meta learners, respectively.

References

A Rauschenberger, E Glaab, and MA van de Wiel (2021). "Predictive and interpretable models via the stacked elastic net". *Bioinformatics*. 37(14):2012-2016. doi:10.1093/bioinformatics/btaa535. <armin.rauschenberger@uni.lu>

Examples

```
set.seed(1)
n <- 50; p <- 100
y <- rnorm(n=n)
X <- matrix(rnorm(n*p), nrow=n, ncol=p)
object <- starnet(y=y, X=X, family="gaussian")
```

weights.starnet

Extract Weights

Description

Extracts coefficients from the meta learner, i.e. the weights for the base learners.

Usage

```
## S3 method for class 'starnet'
weights(object, ...)
```

Arguments

`object` `starnet` object
`...` further arguments (not applicable)

Value

Vector containing intercept and slopes from the meta learner.

Examples

```
set.seed(1)
n <- 50; p <- 100
y <- rnorm(n=n)
X <- matrix(rnorm(n*p),nrow=n,ncol=p)
object <- starnet(y=y,X=X)
weights(object)
```

Index

* **documentation**

starnet-package, [2](#)

.cv.glmnet, [3](#)

.loss, [3](#)

.simulate, [4](#)

auc, [6](#)

coef, [10](#)

coef.starnet, [4](#)

cv.glmnet, [3](#), [6](#), [9](#), [10](#)

cv.starnet, [5](#)

glmnet, [9](#)

glmnet.auc, [6](#)

predict, [10](#)

predict.starnet, [7](#)

print.starnet, [8](#)

starnet, [2](#), [5](#), [7](#), [8](#), [9](#), [10](#)

starnet-package, [2](#)

weights.starnet, [10](#)